

# Rubber Wall Base MSDS Safety Sheet

SECTION 1: IDENTIFICATION OF PRODUCT

TRADE NAME: Rubber Wall Base WHMIS CLASS: NOT CONTROLLED

DESCRIPTION: Rubber, (tpr)

PRODUCT USE: BASE BOARD COVERINGS

TRANSPORT: DOT: Not Regulated

HMIS CODE: HEALTH (0) FIRE (0) REACTIVITY (0) SPECIFIC (0) 0: MINIMAL 1: LIGHT 2:

**MODERATE 3: HIGH 4: DANGEROUS** 

**SECTION 2: HAZARDOUS INGREDIENTS** 

HAZARDOUS INGREDIENTS # CAS % T.L.V. LD50 NONE

**SECTION 3: PHYSICAL PROPERTIES** 

APPEARANCE AND ODOR: Flexible rubber profile extrusions-characteristic rubber odor

BOILING POINT (C): N/A

SPECIFIC GRAVITY (H20=1): 1.6 (APPROX.)

VAPOR DENSITY (Air=1): N/A MELTING POINT (C): N/D EVAPORATION RATE: N/A

SOLUBILITY IN WATER (%): Essentially insoluble

VOLATILE MATTER (% Vol.): N/D

VAPOR PRESSURE (mm of Hg): N/A PH: N/A

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE: YES () NO(X)

AUTO-IGNITION TEMPERATURE (C): Excess 600 F

FLAMMABLE LIMITS (% VOL.IN AIR): LOWER LIMIT: N/D UPPER LIMIT: N/D

EXTINGUISHING MEDIA: WATER SPRAY (X) WATER FOG()

CARBON DIOXIDE (X) FOAM () DRY CHEMICAL (X) OTHERS ()

SPECIAL FIRE FIGHTING PROCEDURES: N/A UNUSUAL FIRE AND EXPLOSION HAZARDS: Hydrogen Chloride Gas liberated in combustion.



Rubber Wall Base MSDS Safety Sheet (Cont' Page 2)

**SECTION 5: REACTIVITY DATA** 

STABILITY: UNSTABLE () STABLE (X)

CONDITIONS TO AVOID: NONE

HAZARDOUS POLYMERIZATION: MAY OCCUR () WILL NOT OCCUR (X)

CONDITIONS TO AVOID: NONE KNOWN

INCOMPATIBILITY (materials to avoid): Avoid contact with acetal or acetal copolymers and with

amine containing materials during processing.

WATER () BASE() OXIDIZING AGENTS () ACID () CORROSIVE () OTHERS ()

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

### **SECTION 6: PREVENTIVE MEASURES**

VENTILATION: When heated provide adequate ventilation to remove smoke and fumes from area.

RESPIRATORY PROTECTION: None required with adequate ventilation.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Gloves

OTHER PROTECTIVE EQUIPMENT: None HANDLING: Practice good personal hygiene.

STORAGE: N/A

### SECTION 7: SPILL OR LEAK PROCEDURES

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Material may be swept, shoveled or vacuumed into containers for reuse or disposal. Use NIOSH approved respiratory equipment where dust is possible.

WASTE DISPOSAL METHOD: Sanitary landfill or incineration in accordance with Federal, State, or local regulations. If incineration is used, recognition should be made that corrosive Hydrogen Chloride is generated.



# Rubber Wall Base MSDS Safety Sheet

**SECTION 8: HEALTH HAZARD DATA** 

ABSORPTION ROUTE: SKIN () EYES () INHALATION () INGESTION ()

EFFECTS OF OVEREXPOSURE:

The ingredients listed in Section 2 are incorporated into the product and will not be released. They are provided for information. No acute effect expected.

SKIN: Contact not expected to be harmful.

EYES: Not expected to be harmful.

INHALATION: Not expected to be harmful.

INGESTION: N/A

**SECTION 9: FIRST AID PROCEDURES** 

SKIN: Wash with soap and water.

EYES: Flush with water and remove the dirt particles.

INHALATION: Move the person to fresh air, give artificial respiration if necessary.

INGESTION: Call a physician.