



## American Flooring Accessories

### Rubber Cove Wall Base Spec Sheet

NYC MEA #72-77-L

Hardness: 85+5

Gauge .125" + 0.15" (1/8")

Dimensional Stability ASTM F1861-01 No more than -0.007 inch (0.6%)

Squareness: 90 + 5

Resistance to heat aging: no fading or softening

Recycled content: 10% standard, up to 85% upon request

DOP free

DEHP free (on the STATE OF CALIFORNIA list of chemicals "known to cause cancer or reproductive toxicity")

May contribute to LEED CI and NC credit MR 4.1, MR 4.2, MR 5.1, MR 5.2

May contribute to LEED MR 5.1 NC/CI Regional Materials: 20% manufactured regionally

May contribute to LEED MR 4.2 Recycled content: 20% (post consumer + ½ post industrial)

ASTM E84-91A: Flame Spread: 50 (class b) Smoke Density: <450

Sizes: 2 ½" (63.5mm), 4" (101.6mm) & 6" (152.4mm) (6" is only available in rolls).

Packed: 120' per carton (36.576m)

Lengths: 4' (1.22m) lengths or 120' (36.576m) continuous rolls

Formats: cove base (top set) & no toe (carpet base)

2 ½", 4" & 6" inside & outside corners available.

Meets ASTM F1861 standard for covebase, rubber Type TP